

PF15P



Key Features

- Perfect Flat, Bezel-Free Pure Glass Multi-Touch Screen
- Spill & Dust Resistant
- Die-Cast Aluminum Housing and Stand
- Sturdy Stand with Cable Management
- Dual Video-In: VGA + DVI
- Wall Mountable (VESA 75 mm)

Specification	
Display Size	15"
Optimal Resolution	1024 x 768
Panel Brightness	250 cd/m ² (typ)
Contrast Ratio	600:1 (typ)
Response Time	8 ms (typ)
Viewing Angle	160° (H)/160° (V)
Input Video Signal	VGA / DVI-D
Touch Technology	Projected Capacitive Touch (USB Interface)
Power Consumption	20W operation / 3W Standby
Input Frequency	Horizontal: 31.5~60.2 kHz; Vertical: 56.3Hz~75Hz
Power Supply	DC 12V +/- 10%
Temperature	Operating: 0°C~40°C; Storage: -10°C~50°C
Humidity	Operating: 20%~80%; Storage: 10%~90%
Weight	4.67 kgs (net)
Physical Dimension	365.2 (W) x 338.6 (H) x 200 (D)
Optional	8.4"/10" 2 nd Display; Wall mount; MSR



Shown mounted on pole

Ultra-Slim Design
only 50 mm (2 in) thick

Splash Resistant

