

# PF615F



### Key Features

- Fanless
- Perfect Flat, Bezel-Free Pure Glass Multi-Touch Screen
- Spill & Dust Resistant
- Wall Mountable (VESA 75 mm)
- Die-Cast Aluminum Housing and Stand
- Sturdy Stand with Cable Management
- Supports 2<sup>nd</sup> Display

### Specification

System	CPU Type	Intel D525 Dual Core, 1.8Ghz, L21M FSB667/800MHz
	Chipset	Intel integrated graphics + ICH8M
	System Memory	1 x DDR3 SO-DIMM socket up to 2GB
	Graphics Memory	Intel GMA 3150 shared system memory up to 256MB
LCD Display & Touch Panel	Size	15" (381 mm)
	Brightness	250 cd/m <sup>2</sup>
	Maximal Resolution	1024 x 768
	Touch Screen Technology	Projected Capacitive Multi-Touch
	Tilt Angle	4~84
Storage	HDD	1 x 2.5" slim SATA HDD/SSD Bay
Audio	Speaker	Internal 2W speaker
I/O Ports	USB	4 ports (V2.0)
	Serial / COM	4 x RJ-45 COM connectors RS-232
	Network	10/100/1000 Mbit Ethernet
	DC Jack	1
	2 <sup>nd</sup> VGA	1
	Cash Drawer	1
Power	Adaptor	65W 19V / 3.4A
Environment	Operation Temperature	5 °C ~ 35 °C (41°F ~ 95 °F)
	Storage Temperature	-20 °C ~ 55 °C (-4 °F ~ 131 °F)
	Operation Humidity	20% ~ 80% RH non condensing
	Storage Humidity	20% ~ 85% RH non condensing
Physical	Dimension (WxHxD)	362 x 375 x 178 mm (14¼" x 14¾" x 7 in)
	Weight (Net)	6.8 kgs
Options	MSR	USB interface
	Mounting	VESA 75 x 75 mm standard mount
	2 <sup>nd</sup> Display	VFD, 8.4" or 10" 2 <sup>nd</sup> display

