

T15RS



Key Features:

- Sleek and stylish design
- UDT (Ultra-Durable Touch) Technology
- Smart Cable Management
- Detachable Stand / Supports VESA mounting
- Spill & dust resistant
- Supports Customer Display & MSR
- Integrated Speakers



Specification	
Display Size	15"
Audio	Integrated speakers
Resolution	1024 (h) x 768 (v)
Brightness	250 cd/m ² (typ)
Contrast Ratio	600:1
Viewing Angle	160° (H) / 160° (V)
Response Time	8 ms (typ)
Input Signal	D-Sub 15 pins / DVI-D
Touch Interface	USB or RS232
Power Consumption	20W operation / 3W standby
Input Frequency	Horizontal: 31.5-60.2 kHz; Vertical: 56.3Hz~75Hz
Power Supply	DC 12V +/-10%
Operation Conditions	Temperature 0°C ~ 40°C, Humidity 20% ~ 80%
Storage Conditions	Temperature -10°C ~ 50°C, Humidity 10% ~ 90%
Dimension (WxHxD)	365.2 (w) x 338.6 (h) x 200 (d)
Weight	4.67 kg (net)
Optional	Customer Display, Wallmount, MSR



RS232, USB, VGA, DVI



Cable management in stand



OSD button control on front



Shown with optional MSR



Rear view (shown with optional MSR)

