

T17R



Shown with optional MSR

Key Features:

- Sleek and stylish design
- UDT (Ultra-Durable Touch) Technology
- Smart Cable Management
- Detachable Stand / Supports VESA mounting
- Spill & dust resistant
- Supports Customer Display & MSR



Specification	
Display Size	17"
Resolution	1280 (h) x 1024 (v)
Brightness	250 cd/m ² (typ)
Contrast Ratio	1000:1 (typ)
LCD Viewing Angle	(L/R/U/D) 85° / 85° / 80° / 80°
Response Time	5 ms (typ)
Input Signal	D-Sub 15 pins / DVI-D
Touch Interface	USB or RS232
Power Consumption	30W
Input Frequency	Horizontal: 31.5-60.2 kHz; Vertical: 56.3Hz~75Hz
Power Supply	DC 12V +/-10%
Operation Conditions	Temperature 0°C ~ 40°C, Humidity 10% ~ 90%
Storage Conditions	Temperature -10°C ~ 50°C, Humidity 10% ~ 90%
Dimension (WxHxD)	399.2 (w) x 381.5 (h) x 200 (d)
Weight	5.86 kg (net)
Optional	7" / 8.4" Customer Display, Wallmount, 3 tracks MSR



Rear view



Side view

