

EP-T883

**Certified
SRM
Compatible**

KEY FEATURES:

- High Speed Printing: 260 mm/s
- Low Cost
- Standard Serial + USB Combo Interface

SPECIFICATIONS

Method	Direct Thermal
Paper Width	79.5± 0.5 mm
Resolution	576 dots/line or 572 dots/line
Printing Speed	260 mm/sec
Interface	Serial/parallel/USB/Serial+USB/LAN
Printing Paper	79.5± 0.5 mm x Φ 83 mm
Line Spacing	3.75 mm (Use command modifies line spacing)
Column Number	80 mm paper: FontA-42 columns or 48 columns/FontB-56 columns or 64 columns / Simplified Chinese, traditional Chinese-21 columns or 24 columns
Character Size	ANK,Font A: 12×24 dots,Font B: 9×17 dots Simplified Chinese, traditional Chinese: 24×24 dots

BARCODE CHARACTER

Barcode types	UPC-A/UPC-E/JAN13, EAN13, /JAN8, EAN8/ CODE39/ITF/CODABAR/CODE93/CODE128
---------------	--

BUFFER

Input buffer	256k bytes
--------------	------------

NV Flash	128k bytes
----------	------------

Cash Drawer Control	DC 24V/1A
---------------------	-----------

POWER SUPPLY

Power Supply	Input: AC 110V/220V, 50-60 Hz
--------------	-------------------------------

Power Adapter	Output: DC 24V/2.5A
---------------	---------------------

PHYSICAL CHARACTERISTICS

Weight	1.70 kg
--------	---------

Dimensions	190 x 145 x 150 mm
------------	--------------------

ENVIRONMENTAL REQUIREMENTS

Operating	Temperature: 0-45° C; Humidity: 10-80%
-----------	--

Storage	Temperature: -10-60 C; Humidity: 10-90%
---------	---



Shown with optional cover



Wall mount available

Interface Cards



Parallel



Serial



USB



LAN



Serial+USB



Receipt



Kitchen



Barcode



PAPER SENSOR



EASY LOAD



COMPACT DESIGN



HIGH SPEED



AUTO-CUTTER



VARIOUS INTERFACE



PAPER WIDTH