

PF615F



Principales Caractéristiques

- Sans Ventilateur
- Écran-Plat sans cadre à surface vitrée multi-tactile
- Résiste aux éclaboussures et à la poussière
- Montage mural (VESA 75 mm)
- Boîtier et socle en aluminium moulé
- Support robuste avec gestion des câbles
- Supporte 2^e affichage

Specification

System	CPU Type	Intel J1900 Celeron Quad Core 2 GHz L2 2M (10W)
	System Memory	1 x DDR3 SO-DIMM socket up to 8GB
	Graphic Engine	Intel Gen7@ >300MHz
	LAN Controller	Realtek RTL8111E-VL-CG 10/100/1000 baseT LAN
	Audio Controller	Realtek ALC662VDO-GR
LCD Display & Touch Panel	Size	15" (381 mm)
	Brightness	250 cd/m ²
	Maximal Resolution	1024 x 768
	Touch Screen Technology	Projected Capacitive Multi-Touch
Storage	HDD	1 x 2.5" SATA HDD / 2.5" SSD (option)
I/O Ports	USB	5 (4x USB 2.0 (A-type); 1x USB 3.0 (A-type))
	Serial / COM	3x RJ-45
	Power Button	1
	DC Jack	1x 4-pin W/lock
	LAN	1x RJ-45 (10/100/1000 baseT)
	VGA	1x DB-15/F
	Cash Drawer	1x RJ-11 (2 in 2 out)
Power	COM	COM1 0V/5/12V; COM2 0V/5V/12V; COM3 0V/5/12V; default BIOS setting 0V
	Cash Drawer	12V/24V; default Jumper setting 24V
	Power Adapter	65W/19V
Environment	Wide Range Power	12V ~ 30V
	Operation Temperature	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20 °C ~ 60 °C (-4 °F ~ 140 °F)
	Operation Humidity	20% ~ 80% RH non condensing
	Storage Humidity	20% ~ 85% RH non condensing
Physical	Dimension (WxHxD)	362 x 375 x 178 mm (14 1/4 x 14 3/4 x 7 in)
	Weight (Net)	6.8 kgs
Certificate	EMC & Safety	FCC Class A; CE; LVD
	OS Support	Windows embedded POSReady 7; Windows 7; Windows embedded 8.1; Industry Pro; Windows 8.1 Pro; Linux
Options	MSR, VESA 75mm, VFD, Mini-LCD 8", 8.4", 10"	



Installation sur poteau



Design ultra-mince de 45 mm



Résiste aux éclaboussures

